



**NOT SUBJECT TO UPDATE
ONCE COPIED / PRINTED
OR DOWNLOADED**

- NOTES
- 1 CT CIRCUITS ARE SHOWN CONNECTED TO RELAY 1 AMP TAP. USE ALTERNATIVE TAP FOR 5AMP RATED CTs.
 - 2 CT & EARTH CONNECTIONS ARE TYPICAL ONLY.
 - 3 METROSILS & SETTING RESISTORS ARE REQUIRED FOR HIGH IMPEDANCE & RESTRICTED E/F APPLICATIONS
 - 4 FOR TERMINAL DIAGRAM SEE 2434W50003 (A2)
 - 5 DRG SHOWS OPTION B (11 OUTPUTS, 5 INPUTS) FOR OPTION C (7 OUTPUTS, 9 INPUTS) SEE 2434W10078 (A3)

MATERIAL:		Copyright © 2000 Reyrolle Ltd.		1	23/3/00	CHANGE NOTED
Dimensions in millimetres : Surface texture in micrometres. Machine where marked ✓ For explanation of dimensions, tolerances, notes etc. see B.S.308. Limit on untoleranced unmachined dimensions ± _____ Limits on untoleranced machined dimensions to B.S.4500; i.e. up to 6±0.1; over 30 to 120±0.3; over 315±0.8; over 6 to 30±0.2; over 120 to 315±0.5; General unmachined angular tolerance ± _____		Finish:	Title:	First used on:	Similar Articles: 2434W10078	
		Treatment:	Reyrolle Protection Hebburn.	Original Scale:	Supersedes:	
				NTS	Drg. No. 2434W10077	
DRAWN M LEASK	CHECKED	APPROVED R.D.WATSON	DATE 23/07/02	IE	OPS	PCP
			Purch.Spec. TQ	EAC	CE	STD
						A3